

On nonlinear controllability and series expansions for Lagrangian systems with dissipative forces

Jorge Cortés , Sonia Martínez
 Instituto de Matemáticas y Física Fundamental
 Consejo Superior de Investigaciones Científicas
 Serrano 123, Madrid, 28006, Spain
 {j.cortes,s.martinez}@imaff.cfmac.csic.es

Francesco Bullo
 Coordinated Science Laboratory
 University of Illinois, Urbana-Champaign
 Urbana, IL 61801, United States
 bullo@uiuc.edu, http://motion.csl.uiuc.edu

Abstract

This note presents series expansions and nonlinear controllability results for Lagrangian systems subject to dissipative forces. The treatment relies on the assumption of dissipative forces of linear isotropic nature. The approach is based on the affine connection formalism for Lagrangian control systems, and on the homogeneity property of all relevant vector fields.

1 Introduction

This note presents novel controllability and perturbation analysis results for control systems with Lagrangian structure. The work belongs to a growing body of research devoted to the geometric control of mechanical systems. We aim to develop coordinate-free analysis and design tools applicable in a unified manner to robotic manipulators, vehicle models, and systems with nonholonomic constraints. Contributions include results on modeling [3, 12], nonlinear controllability [13, 8, 9], series expansions [5], motion planning [6, 16], averaging [2], and passivity-based stabilization [15, 18, 14]. Notions from differential and Riemannian geometry provide the framework underlying these contributions: the formalism of affine connections plays a key role in modeling, analysis and control design for a large class of systems with Lagrangian structure.

The motivation for this work is a standing limitation in the known results on controllability and series expansions. The analysis in [13, 8, 9, 5] applies only to systems subject to no external dissipation, i.e., the system's dynamics is fully determined by the Lagrangian function. With the aim of developing more accurate mathematical models for controlled mechanical systems, this note addresses the setting of dissipative or damping forces. It is worth adding that dissipation is a classic topic in Geometric Mechanics (see for example the work on dissipation induced instabilities [4], the extensive literature on dissipation-based control [15, 18], and recent efforts including [14]).

The contribution of this paper are controllability tests and series expansions that account for a linear isotropic model of dissipation. Remarkably, the same conditions guaranteeing a variety of local accessibility and controllability properties for systems without damping remain valid for the class of systems under consideration. This applies to small-time local controllability, local configuration controllability, and kinematic controllability. Furthermore, we develop a series expansion describing the evolution of the controlled trajectories starting from rest, thus generalizing the work in [5]. The technical approach exploits the homogeneity property of the affine connection model for mechanical control systems.

2 Affine connections and mechanics

In this section we review the notion of affine connection; see [10] for a comprehensive treatment. We introduce a class of Lagrangian systems with dissipative forces and explore their homogeneity properties. All quantities are assumed analytic.

2.1 Affine connections

An *affine connection* on a manifold Q is a map that assigns to a pair of vector fields X, Y another vector field $\nabla_X Y$ such that

$$\begin{aligned} \nabla_{fX+Y} Z &= f\nabla_X Z + \nabla_Y Z \\ \nabla_X (fY + Z) &= (\mathcal{L}_X f)Y + f\nabla_X Y + \nabla_X Z \end{aligned} \quad (1)$$

for any function f and any vector field Z . Usually $\nabla_X Y$ is called the *covariant derivative* of Y with respect to X . Vector fields can also be covariantly differentiated along curves, and this concept will be instrumental in writing the Euler-Lagrange equations. Consider a curve $\gamma: [0, 1] \rightarrow Q$ and a vector field along γ , i.e., a map $v: [0, 1] \rightarrow TQ$ such that $\tau_Q(v(t)) = \gamma(t)$ for all $t \in [0, 1]$ (where $\tau_Q: TQ \rightarrow Q$ denotes the tangent bundle projection). Take now a vector field V that satisfies $V(\gamma(t)) = v(t)$. The *covariant derivative of the vector field v along γ* is defined by

$$\frac{Dv(t)}{dt} = \nabla_{\dot{\gamma}(t)} v(t) = \nabla_{\dot{\gamma}(t)} V(q)|_{q=\gamma(t)}.$$

In particular, we may take $v(t) = \dot{\gamma}(t)$ and set up the equation

$$\nabla_{\dot{\gamma}(t)} \dot{\gamma}(t) = 0. \quad (2)$$

This equation is called the *geodesic equation*, and its solutions are termed the *geodesics* of ∇ . The vector field Z on TQ describing this equation is called the *geodesic spray*.

In a system of local coordinates (q^1, \dots, q^n) , an affine connection is uniquely determined by its *Christoffel symbols* $\Gamma_{ij}^k(q)$, $\nabla_{\frac{\partial}{\partial q^i}} \left(\frac{\partial}{\partial q^j} \right) = \Gamma_{ij}^k \frac{\partial}{\partial q^k}$, and accordingly, the covariant derivative of a vector field is written using (1) as

$$\nabla_X Y = \left(\frac{\partial Y^i}{\partial q^j} X^j + \Gamma_{jk}^i X^j Y^k \right) \frac{\partial}{\partial q^i}.$$

Taking natural coordinates (q^i, v^i) on TQ , the local expression of the geodesic spray reads

$$Z(v_q) = v^i \frac{\partial}{\partial v^i} - \Gamma_{jk}^i(q) v^j v^k \frac{\partial}{\partial v^i}.$$

2.2 Control systems described by affine connections

An *affine connection control system* consists of the following objects: an n -dimensional configuration manifold Q , with $q \in Q$ being the configuration of the system and $v_q \in T_q Q$ being the system's velocity; an affine connection ∇ on Q , with Christoffel symbols $\{\Gamma_{jk}^i : Q \rightarrow \mathbb{R} \mid i, j, k \in \{1, \dots, n\}\}$; and a family of input vector fields $\mathcal{Y} = \{Y_1, \dots, Y_m\}$ on Q . The corresponding equations of motion are written as

$$\nabla_{\dot{q}(t)} \dot{q}(t) = u^a(t) Y_a(q(t)), \quad (3)$$

or, equivalently, in coordinates as

$$\ddot{q}^i + \Gamma_{jk}^i(q) \dot{q}^j \dot{q}^k = u^a(t) Y_a^i(q), \quad (4)$$

where the indexes $i, j, k \in \{1, \dots, n\}$. These equations are a generalization of the Euler-Lagrange equations. If ∇ is the *Levi-Civita affine connection* [10] associated with a kinetic energy metric, then the equations (3) are the forced Euler-Lagrange equations for the associated kinetic energy Lagrangian. If ∇ is the so called *nonholonomic affine connection* [12], the equations (3) represent the forced equations of motion for a nonholonomic system with a kinetic energy Lagrangian, and constraints linear in the velocities.

The systems described by equations (3) are subject to no damping force. However, in a number of situations, friction and dissipation play a relevant role. Consider, for instance, a blimp experiencing the resistance of the air or an underwater vehicle moving in the sea. We introduce a linear isotropic term of dissipation into equations (3), i.e., we consider

$$\nabla_{\dot{q}(t)} \dot{q}(t) = k_d \dot{q}(t) + u^a(t) Y_a(q(t)), \quad (5)$$

where $k_d \in \mathbb{R}$. In local coordinates,

$$\ddot{q}^i + \Gamma_{jk}^i(q) \dot{q}^j \dot{q}^k = k_d \dot{q}^i + u^a(t) Y_a^i(q). \quad (6)$$

This second-order system can be written as a first-order differential equation on the tangent bundle TQ . Using $\{\frac{\partial}{\partial q^i}, \frac{\partial}{\partial v^i}\}$ as a basis for vector fields on the tangent bundle of TQ , we define vector fields L and Y_a^{lift} , $a \in \{1, \dots, m\}$, on TQ by

$$L(v_q) = v^i \frac{\partial}{\partial v^i}, \quad Y_a^{\text{lift}}(v_q) = Y_a^i(q) \frac{\partial}{\partial v^i},$$

so that the control system becomes

$$\dot{v}(t) = Z(v(t)) + k_d L(v(t)) + u^a(t) Y_a^{\text{lift}}(v(t)), \quad (7)$$

where $t \mapsto v(t)$ is now a curve in TQ describing the evolution of a first-order control affine system. We refer to [7] for coordinate-free definitions of the lifting operation $Y_a \rightarrow Y_a^{\text{lift}}$ and of the dilation or Liouville vector field L on TQ .

2.3 Homogeneity and Lie algebraic structure

One fundamental feature of the control systems in equations (3) and (5) is the polynomial dependence of the vector fields Z , L and Y^{lift} on the velocity variables v^i . As shown in [7], this structure leads to remarkable simplifications in the iterated Lie brackets between the vector fields $\{Z, Y_1^{\text{lift}}, \dots, Y_m^{\text{lift}}\}$. This fact is the enabling property for the controllability analyses in [13] and the series expansion in [5]. As we shall see below, these simplifications also take place between the vector fields $\{Z + k_d L, Y_1^{\text{lift}}, \dots, Y_m^{\text{lift}}\}$.

We start by introducing the notion of *geometric homogeneity* as described in [11]: given two vector fields X and X_E , the vector field X is *homogeneous with degree $m \in \mathbb{Z}$ with respect to X_E* if $[X_E, X] = mX$.

Lemma 2.1 *Let ∇ be an affine connection on Q with geodesic spray Z , and let Y be a vector field on Q . Then $[L, Z] = (+1)Z$ and $[L, Y^{\text{lift}}] = (-1)Y^{\text{lift}}$.*

In the following, a vector field X on TQ is simply *homogeneous of degree $m \in \mathbb{Z}$* if it is homogeneous of degree m with respect to L . Let \mathcal{P}_j be the set of vector fields on TQ of homogeneous degree j , so that $Z \in \mathcal{P}_1$ and $Y^{\text{lift}} \in \mathcal{P}_{-1}$. One can see that $[L, X] = 0$, for all $X \in \mathcal{P}_0$, and that $[\mathcal{P}_i, \mathcal{P}_j] \subset \mathcal{P}_{i+j}$.

3 Nonlinear controllability

In this section we investigate the controllability properties of systems with isotropic dissipation. We analyse local accessibility, controllability, and kinematic controllability.

3.1 Local accessibility and controllability

Here we study conditions for accessibility and controllability of mechanical systems with dissipation. The notion of configuration controllability concerns the reachable set restricted to the configuration space Q and is weaker than full-state controllability; we refer the reader to [13] for the exact definitions.

We start by introducing some notation. Let $\overline{\text{Lie}}(\mathbf{Y})$ and $\overline{\text{Sym}}(\mathbf{Y})$ denote the involutive and the symmetric closure, respectively, of the set of vector fields $\mathbf{Y} = \{Y_1, \dots, Y_m\}$. Let also \mathbf{Y}^{lift} denote the set of lifted vector fields $\{Y_1^{\text{lift}}, \dots, Y_m^{\text{lift}}\}$. The next proposition show that the involutive closure of the system (3) at zero velocity is the same as the one of (5).

Proposition 3.1 *Consider the distributions*

$$\mathcal{D}_{(1)} = \text{span}\{Z, \mathbf{Y}^{\text{lift}}\}, \quad \mathcal{D}_{(1)}^L = \text{span}\{Z + k_d L, \mathbf{Y}^{\text{lift}}\}.$$

Define recursively

$$\begin{aligned} \mathcal{D}_{(k)} &= \mathcal{D}_{(k-1)} + [\mathcal{D}_{(k-1)}, \mathcal{D}_{(k-1)}], \\ \mathcal{D}_{(k)}^L &= \mathcal{D}_{(k-1)}^L + [\mathcal{D}_{(k-1)}^L, \mathcal{D}_{(k-1)}^L], \quad k \geq 2. \end{aligned}$$

Then, $\mathcal{D}_{(k)}(0_q) = \mathcal{D}_{(k)}^L(0_q)$, for all k . Consequently, the accessibility distributions $\mathcal{D}_{(\infty)}(0_q) = \overline{\text{Lie}}(Z, \mathbf{Y}^{\text{lift}})_q$ and $\mathcal{D}_{(\infty)}^L(0_q) = \overline{\text{Lie}}(Z + k_d L, \mathbf{Y}^{\text{lift}})_q$ coincide.

Proof: Obviously $\mathcal{D}_{(1)}(0_q) = \mathcal{D}_{(1)}^L(0_q)$. Moreover, we have $[\mathcal{D}_{(1)}, \mathcal{D}_{(1)}] \subset \mathcal{D}_{(2)}^L$ and $[\mathcal{D}_{(1)}^L, \mathcal{D}_{(1)}^L] \subset \mathcal{D}_{(2)}$, since

$$[Z + k_d L, Y^{\text{lift}}] = [Z, Y^{\text{lift}}] - k_d Y^{\text{lift}}.$$

Let us assume that

$$\mathcal{D}_{(k)}(0_q) = \mathcal{D}_{(k)}^L(0_q), \quad (8)$$

$$[\mathcal{D}_{(k)}, \mathcal{D}_{(k)}] \subset \mathcal{D}_{(k+1)}^L, \quad (9)$$

$$[\mathcal{D}_{(k)}^L, \mathcal{D}_{(k)}^L] \subset \mathcal{D}_{(k+1)}. \quad (10)$$

hold for k and let us show that (8-10) are valid for $k+1$. We have

$$\begin{aligned} \mathcal{D}_{k+1} &= \mathcal{D}_{(k)} + [\mathcal{D}_{(k)}, \mathcal{D}_{(k)}] \subset \mathcal{D}_{(k)} + \mathcal{D}_{(k+1)}^L \implies \\ \mathcal{D}_{k+1}(0_q) &\subset \mathcal{D}_{(k)}(0_q) + \mathcal{D}_{(k+1)}^L(0_q) = \mathcal{D}_{(k)}^L(0_q) + \mathcal{D}_{(k+1)}^L(0_q) \\ &= \mathcal{D}_{(k+1)}^L(0_q). \end{aligned}$$

Similarly, we can prove $\mathcal{D}_{k+1}^L(0_q) \subset \mathcal{D}_{(k+1)}(0_q)$, and thus $\mathcal{D}_{(k+1)}(0_q) = \mathcal{D}_{(k+1)}^L(0_q)$. On the other hand,

$$\begin{aligned} [\mathcal{D}_{(k+1)}^L, \mathcal{D}_{(k+1)}^L] &= [\mathcal{D}_{(k)}^L + [\mathcal{D}_{(k)}^L, \mathcal{D}_{(k)}^L], \mathcal{D}_{(k)}^L + [\mathcal{D}_{(k)}^L, \mathcal{D}_{(k)}^L]] \\ &\subset [\mathcal{D}_{(k)}^L + \mathcal{D}_{(k+1)}, \mathcal{D}_{(k)}^L + \mathcal{D}_{(k+1)}] \\ &\subset \mathcal{D}_{(k+1)} + [\mathcal{D}_{(k)}^L, \mathcal{D}_{(k+1)}] + \mathcal{D}_{(k+2)} \\ &= [\mathcal{D}_{(k)}^L, \mathcal{D}_{(k+1)}] + \mathcal{D}_{(k+2)}. \end{aligned}$$

Thus, it remains to be checked that $[\mathcal{D}_{(k)}^L, \mathcal{D}_{(k+1)}] \subset \mathcal{D}_{(k+2)}$. Observe that

$$\begin{aligned} [\mathcal{D}_{(k)}^L, \mathcal{D}_{(k+1)}] &= [\mathcal{D}_{(k-1)}^L + [\mathcal{D}_{(k-1)}^L, \mathcal{D}_{(k-1)}^L], \mathcal{D}_{(k+1)}] \\ &\subset [\mathcal{D}_{(k-1)}^L, \mathcal{D}_{(k+1)}] + \mathcal{D}_{(k+2)}, \end{aligned}$$

where we have used the induction hypothesis on (10), i.e. $[\mathcal{D}_{(k-1)}^L, \mathcal{D}_{(k-1)}^L] \subset \mathcal{D}_{(k)}$. By a recursive argument, we find that what we must show is $[\mathcal{D}_{(1)}^L, \mathcal{D}_{(k+1)}] \subset \mathcal{D}_{(k+2)}$. Clearly, $[Y_i^{\text{lift}}, \mathcal{D}_{(k+1)}] \subset \mathcal{D}_{(k+2)}$, $i \in \{1, \dots, m\}$. In addition,

$$[Z + k_d L, \mathcal{D}_{(k+1)}] = [Z, \mathcal{D}_{(k+1)}] + [k_d L, \mathcal{D}_{(k+1)}] \subset \mathcal{D}_{(k+2)},$$

since $[L, X] \in \mathcal{D}_{(k+1)}$, for all $X \in \mathcal{D}_{(k+1)}$, by homogeneity. Finally, it can be similarly shown using (9) that $[\mathcal{D}_{(k+1)}, \mathcal{D}_{(k+1)}] \subset \mathcal{D}_{(k+2)}^L$. Thus, (8-10) are satisfied for all k . \blacksquare

Corollary 3.2 *Consider a mechanical control system of the form (5). Then*

- (i) *the system is locally accessible (LA) at q starting with zero velocity if $\overline{\text{Sym}}(\mathbf{Y})_q = T_q Q$,*
- (ii) *the system is locally configuration accessible (LCA) at $q \in Q$ if $\overline{\text{Lie}}(\overline{\text{Sym}}(\mathbf{Y}))_q = T_q Q$.*

Proof: The manifold Q can be identified with the set of zero vectors $Z(TQ)$ of TQ by the diffeomorphism $q \mapsto 0_q$. Hence, the tangent space to $Z(TQ)$ at 0_q is isomorphic to $T_q Q$. On the other hand, the natural projection $\tau_Q : TQ \rightarrow Q$ defines the set \mathcal{V} as the kernel of $T\tau_Q : TTQ \rightarrow TQ$. One has that \mathcal{V}_{0_q} is isomorphic to $T_q Q$. Both parts give us the natural decomposition

$$T_{0_q} TQ = T_{0_q}(Z(TQ)) \oplus \mathcal{V}_{0_q} \simeq T_q Q \oplus T_q Q.$$

The result follows from the former proposition and Proposition 5.9 in [13] which asserts that $\mathcal{D}_{(\infty)}(0_q) \cap \mathcal{V}_{0_q} = \overline{\text{Sym}}(\mathbf{Y})_q^{\text{lift}}$ and $\mathcal{D}_{(\infty)}(0_q) \cap T_{0_q}(Z(TQ)) = \overline{\text{Lie}}(\overline{\text{Sym}}(\mathbf{Y}))_q$. \blacksquare

Next, we examine the small-time local controllability properties of the system in equation (5). We shall use the following conventions. The *degree* of an iterated Lie bracket is equal to the number of its factors. The degree of B in $\{X_0, X_1, \dots, X_m\}$ is given by $\delta(B) = \delta_0(B) + \delta_1(B) + \dots + \delta_m(B)$, where $\delta_i(B)$ is the number of times the factor X_i appears. A Lie bracket B in $\{X_0, X_1, \dots, X_m\}$ is *bad* if $\delta_0(B)$ is odd and $\delta_i(B)$ is even, $i \in \{1, \dots, m\}$, where $\delta_a(B)$ denotes the number of times that X_a occurs in B . Otherwise, B is *good*.

The results in [13, 17] include sufficient conditions for small-time local controllability (STLC) and small-time

local configuration controllability (STLCC). Let the system be LA at $q \in Q$ starting with zero velocity (resp. LCA at $q \in Q$). The system in equation (5) is STLC at q starting with zero velocity (resp. STLCC) if:

(Sussmann's criterium on $\{Z + k_d L, \mathcal{Y}^{\text{lifft}}\}$):

Every bad bracket B in $\{Z + k_d L, \mathcal{Y}^{\text{lifft}}\}$ is a \mathbb{R} -linear combination of good brackets evaluated at 0_q of lower degree than B .

We shall show that if the conditions for STLC and STLCC are satisfied for the set $\{Z, \mathcal{Y}^{\text{lifft}}\}$, then they are also verified for the set $\{Z + k_d L, \mathcal{Y}^{\text{lifft}}\}$. We illustrate this fact by considering two low order settings. First, every bracket B of order 1 or 2, i.e., $\delta(B) \leq 2$, is good. In addition, $[Z + k_d L, Y^{\text{lifft}}] = [Z, Y^{\text{lifft}}] - k_d Y^{\text{lifft}}$, and therefore, every good bracket in $\{Z + k_d L, \mathcal{Y}^{\text{lifft}}\}$ of degree 2 is the sum of the corresponding good bracket in $\{Z, \mathcal{Y}^{\text{lifft}}\}$ plus some good brackets of lower degree in $\{Z + k_d L, \mathcal{Y}^{\text{lifft}}\}$.

Proposition 3.3 *Assume Sussmann's criterium on $\{Z, \mathcal{Y}^{\text{lifft}}\}$. Then*

- (i) *every bad bracket B in $\{Z + k_d L, \mathcal{Y}^{\text{lifft}}\}$ of degree k , evaluated at 0_q , is a \mathbb{R} -linear combination of good brackets of lower degree,*
- (ii) *every good bracket C in $\{Z + k_d L, \mathcal{Y}^{\text{lifft}}\}$ of degree k , evaluated at 0_q , is a \mathbb{R} -linear combination of the corresponding good bracket in $\{Z, \mathcal{Y}^{\text{lifft}}\}$ and of some brackets in $\{Z + k_d L, \mathcal{Y}^{\text{lifft}}\}$ of lower degree,*
- (iii) *every good bracket in $\{Z, \mathcal{Y}^{\text{lifft}}\}$ of degree k , evaluated at 0_q , is a \mathbb{R} -linear combination of good brackets in $\{Z + k_d L, \mathcal{Y}^{\text{lifft}}\}$ of degree $\leq k$.*

For reasons of brevity, we do not report the proof here.

If P is a symmetric product of vector fields in \mathcal{Y} , we let $\gamma_a(P)$ denote the number of occurrences of Y_a in P . The degree of P will be $\gamma_1(P) + \dots + \gamma_m(P)$. We shall say that P is *bad* if $\gamma_a(P)$ is even for each $a \in \{1, \dots, m\}$. We say that P is *good* if it is not bad.

Corollary 3.4 *Consider a mechanical control system as in (5). Then, we have*

- (i) *the system is STLC at $q \in Q$ starting with zero velocity if $\overline{\text{Sym}(\mathcal{Y})}_q = T_q Q$ and every bad symmetric product B in $\overline{\text{Sym}(\mathcal{Y})}_q$ is a linear combination of good symmetric products of lower degree, and*

- (ii) *the system is STLCC at $q \in Q$ if $\overline{\text{Lie}(\overline{\text{Sym}(\mathcal{Y})})}_q = T_q Q$ and every bad symmetric product B in $\overline{\text{Sym}(\mathcal{Y})}_q$ is a linear combination of good symmetric products of lower degree.*

Proof: It follows from the 1 – 1 correspondence between bad (resp. good) Lie brackets in $\{Z, \mathcal{Y}^{\text{lifft}}\}$ and bad (resp. good) symmetric products in \mathcal{Y} ; see [13]. ■

3.2 Kinematic controllability

Kinematic controllability [8] has direct relevance to the trajectory planning problem for mechanical systems of the form (3). This section presents a generalized notion of kinematic controllability for affine connection systems with isotropic dissipation. Consider the mechanical system (5), and let \mathcal{I} is the distribution generated by the input vector fields $\{Y_1, \dots, Y_m\}$. A controlled solution to (5) is a curve $t \mapsto q(t) \in Q$ satisfying

$$\nabla_{\dot{q}} \dot{q} - k_d \dot{q} \in \mathcal{I}_{q(t)}. \quad (11)$$

Let $s : [0, T] \rightarrow [0, 1]$ be a twice-differentiable function such that $s(0) = 0, s(T) = 1, \dot{s}(0) = \dot{s}(T) = 0$, and $\dot{s}(t) > 0$ for all $t \in (0, T)$. We call such a curve s a *time scaling*. A vector field V is a *decoupling vector field* for the system (5) if, for any time scaling s and for any initial condition q_0 , the curve $t \mapsto q(t)$ on Q solving

$$\dot{q}(t) = \dot{s}(t)V(q(t)), \quad q(0) = q_0, \quad (12)$$

satisfies the conditions in (11). The integral curves of V on the time interval $[0, 1]$ are called *kinematic motions*.

Lemma 3.5 *The vector field V is decoupling for the mechanical system (5) if and only if $V \in \mathcal{I}$ and $\langle V : V \rangle \in \mathcal{I}$.*

Proof: Given a curve $\gamma : [0, T] \rightarrow Q$ satisfying equation (12), we compute

$$\nabla_{\dot{\gamma}} \dot{\gamma} = \ddot{s}V + \dot{s}\nabla_{\dot{\gamma}} V = \ddot{s}V + \dot{s}^2 \nabla_V V,$$

where we used the identities (1) for vector fields along curves; see [10]. Next, the curve γ is a kinematic motion if, for all time scalings s , the constraints (11) are satisfied. Thus

$$\nabla_{\dot{\gamma}} \dot{\gamma} - k_d \dot{\gamma} = (\ddot{s} - k_d \dot{s})V + \frac{\dot{s}^2}{2} \langle V : V \rangle \in \mathcal{I}.$$

Since s and $\gamma(0)$ are arbitrary, V and $\langle V : V \rangle$ must separately belong to the input distribution \mathcal{I} . The other implication is trivial. ■

We say that the system (5) is *locally kinematically controllable* if for any $q \in Q$ and any neighborhood U_q of q , the set of reachable configurations from q by kinematic motions remaining in U_q contains q in its interior.

Lemma 3.6 *The system (5) is locally kinematically controllable if there exist $p \in \{1, \dots, m\}$ vector fields $\{V_1, \dots, V_p\} \subset \mathcal{I}$ such that*

- (i) $\langle V_c : V_c \rangle \in \mathcal{I}$, for all $c \in \{1, \dots, p\}$, and
- (ii) $\overline{\text{Lie}}(V_1, \dots, V_p)$ has rank n at all $q \in Q$.

4 Series expansion for the forced evolution

The result in this section extends the treatment in [5]. Consider the system (5) with initial condition $\dot{q}(0) = 0$.

Proposition 4.1 *Given any integrable input vector field $(q, t) \mapsto Y(q, t)$, let $k \geq 2$, and define*

$$V_1(q, t) = \int_0^t e^{k_d(t-\tau)} Y(q, \tau) d\tau,$$

$$V_k(q, t) = -\frac{1}{2} \sum_{j=1}^{k-1} \int_0^t e^{k_d(t-\tau)} \langle V_j(q, \tau) : V_{k-j}(q, \tau) \rangle d\tau.$$

There exists a $T > 0$ such that the series $(q, t) \mapsto \sum_{k=1}^{+\infty} V_k(q, t)$ converges absolutely and uniformly for $t \in [0, T]$ and for q in an appropriate neighborhood of q_0 . Over the same interval, the solution $\gamma : [0, T] \rightarrow Q$ to the system (5) with $\dot{\gamma}(0) = 0$ satisfies

$$\dot{\gamma} = \sum_{k=1}^{+\infty} V_k(\gamma, t). \quad (13)$$

Proof: *Step I.* A time-varying vector field $(q, t) \mapsto X(q, t)$ gives rise to the initial value problem on Q

$$\dot{q}(t) = X(q, t), \quad q(0) = q_0.$$

We denote its solution at time T via $q(T) = \Phi_{0,T}^X(q_0)$, and we refer to it as the flow of X . Next, consider

$$\dot{q}(t) = X(q, t) + Y(q, t), \quad q(0) = q_0,$$

where X and Y are analytic (in q) time-varying vector fields. If we regard X as a perturbation to the vector field Y , we can describe the flow of $X + Y$ in terms of a nominal and perturbed flow. The following relationship is referred to as the *variation of constants* formula [1] and describes the perturbed flow:

$$\Phi_{0,t}^{X+Y} = \Phi_{0,t}^Y \circ \Phi_{0,t}^{(\Phi_{0,t}^Y)^* X}, \quad (14)$$

where, given any vector field X and any diffeomorphism ϕ , the $\phi^* X$ is the pull-back of X along ϕ . In particular, the pull-back along the flow of a vector field admits the following series expansion representation [1]

$$(\Phi_{0,t}^Y)^* X(q, t) = X(q, t) + \sum_{k=1}^{+\infty} \int_0^t \dots \int_0^{s_{k-1}} (\text{ad}_{Y(q, s_k)} \dots \text{ad}_{Y(q, s_1)} X(q, t)) ds_k \dots ds_1. \quad (15)$$

Step II. In equation (7), let the Liouville vector field play the role of the perturbation to the vector field $Z + Y^{\text{lift}}$. Then the application of (14) yields $\Phi^{Z+k_dL+Y^{\text{lift}}} = \Phi^{k_dL} \circ \Phi^\Delta$, where we compute $\Phi^{k_dL}(q_0, v_0) = (q_0, e^{k_d t} v_0)$, and where the homogeneity leads to

$$\begin{aligned} \Delta &= \sum_{k=0}^{+\infty} \frac{t^k}{k!} \text{ad}_{k_dL}^k(Z + Y^{\text{lift}}) = \sum_{k=0}^{+\infty} \frac{(k_d t)^k}{k!} \text{ad}_L^k(Z + Y^{\text{lift}}) \\ &= \sum_{k=0}^{+\infty} \frac{(k_d t)^k}{k!} (Z + (-1)^k Y^{\text{lift}}) \\ &= \sum_{k=0}^{+\infty} \left(\frac{(k_d t)^k}{k!} Z + \frac{(-k_d t)^k}{k!} Y^{\text{lift}} \right) = e^{k_d t} Z + e^{-k_d t} Y^{\text{lift}}. \end{aligned}$$

Let $Z' = e^{k_d t} Z$, and accordingly $\langle X_1 : X_2 \rangle' = e^{k_d t} \langle X_1 : X_2 \rangle$. The initial value problem associated with Δ is therefore

$$\dot{y} = Z'(y) + e^{-k_d t} Y(y, t)^{\text{lift}}, \quad (16)$$

where we let $y = (r, \dot{r})$.

Step III. Let $k \in \mathbb{N}$ and consider the equation

$$\dot{y}_k = (Z' + [X_k^{\text{lift}}, Z'] + Y_k^{\text{lift}})(y_k, t). \quad (17)$$

We recover (16) by setting $k = 1$, $X_1 = 0$, $Y_1 = e^{-k_d t} Y(q, t)$, and accordingly $y(t) = y_1(t)$. We can now see the vector field $Z' + [X_k^{\text{lift}}, Z']$ as the perturbation to Y_k^{lift} . Using (14) and (15), we set $y_k(t) = \Phi_{0,t}^{Y_k^{\text{lift}}}(y_{k+1}(t))$. Some manipulations based on the homogeneity properties of the vector fields lead to

$$\begin{aligned} \dot{y}_{k+1}(t) &= \left(\left(\Phi_{0,t}^{Y_k^{\text{lift}}} \right)^* (Z' + [X_k^{\text{lift}}, Z']) \right) (y_{k+1}(t)) \\ &= Z' + [X_k^{\text{lift}} + \bar{Y}_k^{\text{lift}}, Z'] - e^{-k_d t} \langle \bar{Y}_k : X_k \rangle^{\text{lift}} \\ &\quad - \frac{e^{k_d t}}{2} \langle \bar{Y}_k : \bar{Y}_k \rangle^{\text{lift}}. \end{aligned}$$

Therefore, the differential equation for $y_{k+1}(t)$ is of the same form as (17), where

$$X_{k+1} = X_k + \bar{Y}_k, \quad Y_{k+1} = -e^{k_d t} \left\langle \bar{Y}_k : X_k + \frac{1}{2} \bar{Y}_k \right\rangle.$$

We easily compute $X_k = \sum_{m=1}^{k-1} \bar{Y}_m$ and set

$$Y_{k+1} = -e^{k_d t} \left\langle \bar{Y}_k : \sum_{m=1}^{k-1} \bar{Y}_m + \frac{1}{2} \bar{Y}_k \right\rangle.$$

One can iterate this procedure as in the case of no dissipation [5] to obtain the formal expansion

$$\begin{aligned} \dot{r} &= \sum_{k=1}^{+\infty} V'(r, t), \quad V_1'(r, t) = \int_0^t e^{-k_d \tau} Y(r, \tau) d\tau, \\ V_k'(r, t) &= -\frac{1}{2} \sum_{j=1}^{k-1} \int_0^t e^{k_d \tau} \langle V_j'(r, \tau) : V_{k-j}'(r, \tau) \rangle d\tau. \end{aligned}$$

To obtain the flow of $Z + k_d L + Y^{\text{lift}}$, we compose the flow of Δ with that of $k_d L$ to compute

$$\dot{q} = e^{k_d t} \dot{r} = \sum_{k=1}^{+\infty} V(q, t), \quad V_1(q, t) = \int_0^t e^{k_d(t-\tau)} Y(q, \tau) d\tau,$$

$$V_k(q, t) = -\frac{1}{2} \sum_{j=1}^{k-1} \int_0^t e^{k_d(\tau-2\tau+t)} \langle V_j(q, \tau) : V_{k-j}(q, \tau) \rangle d\tau.$$

Step IV. Select a coordinate chart around q_0 . In this way, we can locally identify Q with \mathbb{R}^n . Define $B_\sigma(q_0) = \{z \in \mathbb{C}^n : \|z - q_0\| < \sigma\}$. Resorting to the analysis in [5], it can be proven that there exists a $L > 0$ such that $\|V_k\|_{\sigma'} \leq L^{1-k} \|Y\|_\sigma (te^{k_d t})^{2k-1}$, where $\sigma' < \sigma$, $\|\cdot\|_{\sigma'}$ denotes

$$\|Y\|_\sigma = \max_{s \in [0, t]} \max_{i \in \{1, \dots, n\}} \max_{z \in B_\sigma(q_0)} |Y^i(q, s)|,$$

and Y^i is the i th component of Y with respect to the coordinate basis. Hence, for $\|Y\|_\sigma T^2 e^{2k_d T} < L$, the previous expansion converges absolutely and uniformly in $t \in [0, T]$ and $q \in B_{\sigma'}(q_0)$. ■

5 Conclusions

This paper extends previous results on nonlinear controllability and series expansions for mechanical systems for the setting of isotropic dissipation.

Acknowledgments

The first two authors' work was funded by FPU and FPI grants from the Spanish Ministerio de Ciencia y Tecnología and Ministerio de Educación y Cultura, respectively. The third author's work was supported in part by NSF grant CMS-0100162.

References

[1] A. A. Agrachev and R. V. Gamkrelidze. The exponential representation of flows and the chronological calculus. *Math. USSR Sbornik*, 35(6):727–785, 1978.

[2] J. Baillieul. Stable average motions of mechanical systems subject to periodic forcing. In M. J. Enos, editor, *Dynamics and Control of Mechanical Systems: The Falling Cat and Related Problems*, volume 1, pages 1–23. Field Institute Communications, 1993.

[3] A. M. Bloch and P. E. Crouch. Nonholonomic control systems on Riemannian manifolds. *SIAM Journal on Control and Optimization*, 33(1):126–148, 1995.

[4] A. M. Bloch, P. S. Krishnaprasad, J. E. Marsden, and T. S. Ratiu. Dissipation induced instabilities. *Annales de l'Institut Henri Poincaré analyse non linéaire*, 11 (1):37–90, 1994.

[5] F. Bullo. Series expansions for the evolution of mechanical control systems. *SIAM Journal on Control and Optimization*, 40(1):166–190, 2001.

[6] F. Bullo, N. E. Leonard, and A. D. Lewis. Controllability and motion algorithms for underactuated Lagrangian systems on Lie groups. *IEEE Transactions on Automatic Control*, 45(8):1437–1454, 2000.

[7] F. Bullo and A. D. Lewis. On the homogeneity of the affine connection model for mechanical control systems. In *IEEE Conf. on Decision and Control*, pages 1260–1265, Sydney, Australia, December 2000.

[8] F. Bullo and K. M. Lynch. Kinematic controllability for decoupled trajectory planning in underactuated mechanical systems. *IEEE Transactions on Robotics and Automation*, 17(4):402–412, 2001.

[9] J. Cortés, S. Martínez, J. P. Ostrowski, and H. Zhang. Simple mechanical control systems with constraints and symmetry. *SIAM Journal on Control and Optimization*, 2000. To appear.

[10] M. P. Do Carmo. *Riemannian Geometry*. Birkhäuser Verlag, Boston, MA, 1992.

[11] M. Kawski. Geometric homogeneity and applications to stabilization. In *Symposium on Nonlinear Control Systems*, pages 251–256, Tahoe City, CA, July 1995.

[12] A. D. Lewis. Simple mechanical control systems with constraints. *IEEE Transactions on Automatic Control*, 45(8):1420–1436, 2000.

[13] A. D. Lewis and R. M. Murray. Configuration controllability of simple mechanical control systems. *SIAM Journal on Control and Optimization*, 35(3):766–790, 1997.

[14] M. C. Muñoz-Lecanda and F.J. Yániz. Dissipative control of mechanical systems: a geometric approach. *SIAM Journal on Control and Optimization*, 40(5):1505–1516, 2002.

[15] R. Ortega, A. Loria, P. J. Nicklasson, and H. Sira-Ramirez. *Passivity-Based Control of Euler-Lagrange Systems: Mechanical, Electrical and Electromechanical Applications*. Communications and Control Engineering. Springer Verlag, New York, 1998.

[16] J. P. Ostrowski. Steering for a class of dynamic nonholonomic systems. *IEEE Transactions on Automatic Control*, 45(8):1492–1497, 2000.

[17] H. J. Sussmann. A general theorem on local controllability. *SIAM Journal on Control and Optimization*, 25(1):158–194, 1987.

[18] A. J. van der Schaft. *L2-Gain and Passivity Techniques in Nonlinear Control*. Springer Verlag, New York, 2 edition, 1999.